

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
14 April 2005 (14.04.2005)

PCT

(10) International Publication Number  
**WO 2005/032985 A1**

(51) International Patent Classification<sup>7</sup>: **B65G 43/06**

(21) International Application Number:  
PCT/IB2004/003188

(22) International Filing Date:  
30 September 2004 (30.09.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2003/7667 1 October 2003 (01.10.2003) ZA

(71) Applicant and

(72) Inventor: BARNARD, Hubert de Villiers [ZA/ZA]; 103  
van der Merwe Street, Silverton Ridge, 0184 Pretoria (ZA).

(74) Agents: DONALD, Heather, June? et al.; Spoor &  
Fisher, P. O. Box 41312, Craighall, 2146 Morningside  
(ZA).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.


(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,  
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: CONVEYER BELT BRAKE



(57) Abstract: Conveyor belt braking apparatus comprises an idler roller (10) rotatable about an axle, and a brake member (40) mounted adjacent the idler roller and movable relative to the roller between a first, inoperative position adjacent a belt supported by the roller and a second, braking position against the belt. An operating mechanism (26, 28) is arranged to sense the direction of rotation of the roller and to move the brake member from the first, inoperative position to the second, braking position when the direction of rotation of the roller reverses in use. Preferably the mechanism includes a clutch bearing (26) that engages to move the brake member from the first inoperative position to the second, braking position thereof when the roller reverses direction.



WO 2005/032985 A1